



Elevator 2xSchuko	Elevator 2xSchuko
<p><b>Beschreibung:</b></p> <ul style="list-style-type: none"> <li>• Versenk- und herausfahrbare Elektrifizierungseinheit für den Einbau in Küchenarbeitsplatten wie Holz, Schichtstoff, Naturstein oder Glas bzw. in Bürotische.</li> <li>• Nach leichtem Druck auf den Deckel fährt die Einheit dank eines Federmechanismus aus und bietet eine komfortable und sichere Stromzufuhr über eine Schutzkontakt- und zwei Euro-Steckdosen.</li> <li>• Einfaches und flächenbündiges Versenken bei Nichtgebrauch.</li> <li>• Befestigung mittels Schraubring.</li> </ul>	<p><b>Description:</b></p> <ul style="list-style-type: none"> <li>• Ascending and descending electrification unit for installation for kitchen worktops like wood, laminated plastic, natural stone or glass resp. in office and conference tables.</li> <li>• When pushing the lid the unit ascends due to a spring mechanism and offers a convenient and safe power supply via one German type and two Euro type sockets.</li> <li>• Simple and plain descending when not used.</li> <li>• Mounting via ring nut.</li> </ul>
<p><b>Steckdosen:</b></p> <ul style="list-style-type: none"> <li>• Nach IEC 60884, VDE 0620-1</li> <li>• 2-polig mit Schutzkontakt</li> <li>• 16A/3680W, AC250V, IP20, mit Kinderschutz</li> <li>• Schwarz</li> </ul>	<p><b>Sockets:</b></p> <ul style="list-style-type: none"> <li>• According IEC 60884, VDE 0620-1</li> <li>• 2-pole with earthing contact</li> <li>• 16A/3680W, AC250V, IP20, with child protection</li> <li>• Black</li> </ul>
<p><b>Anschluss:</b></p> <ul style="list-style-type: none"> <li>• 2,0m H05VV-F 3G1,5mm<sup>2</sup> schwarz mit offenen Enden und Aderendhülsen</li> </ul>	<p><b>Connection:</b></p> <ul style="list-style-type: none"> <li>• 2,0m H05VV-F 3G1,5mm<sup>2</sup> black with endsleeves</li> <li>• German type mounting plug black enclosed</li> </ul>

<ul style="list-style-type: none"> <li>Mit beigelegtem Schutzkontakt-Montagestecker schwarz</li> </ul>	
<b>Befestigung:</b> <ul style="list-style-type: none"> <li>In rundem Ausschnitt mit <math>\varnothing 80\text{mm}</math> (+/-1mm)</li> <li>Für Plattenstärken von 16mm bis 60mm</li> <li>Fixierung über Schraubring</li> </ul>	<b>Mounting:</b> <ul style="list-style-type: none"> <li>In round hole with <math>\varnothing 80(+/-1)\text{mm}</math></li> <li>For mounting in plates with thicknesses from 16mm to 60mm</li> <li>Mounting via ring nut.</li> </ul>
<b>Material:</b> <ul style="list-style-type: none"> <li>Kunststoff: Schwarz, PA6 GF 30 V1 , Glühdraht-Prüfung bis 850°C</li> <li>Profil: Aluminium glänzend poliert, „Edelstahl-Look“, Strangguss</li> <li>Blenden: Edelstahl gestanzt und gebürstet</li> </ul>	<b>Material:</b> <ul style="list-style-type: none"> <li>Plastic: Black, PA6 GF 30 V1 , glow wire resistant up to 850°C</li> <li>Profile: Aluminum polished "stainless steel look", continuous casting</li> <li>Aperture: Stainless steel brushed and stamped</li> </ul>
<b>Abmessungen in mm:</b> <ul style="list-style-type: none"> <li>Siehe Zeichnung</li> </ul>	<b>Measurements in mm:</b> <ul style="list-style-type: none"> <li>According to drawing</li> </ul>
<b>Lieferform:</b> <ul style="list-style-type: none"> <li>In Kartonbox verpackt</li> </ul>	<b>Packing:</b> <ul style="list-style-type: none"> <li>In carton box</li> </ul>
<b>Lieferumfang:</b> <ul style="list-style-type: none"> <li>1x Elevator</li> <li>1x Montageanleitung</li> </ul>	<b>Extent of delivery:</b> <ul style="list-style-type: none"> <li>1x Elevator</li> <li>1x Mounting instruction</li> </ul>